

# Proceedings of the Iowa Academy of Science

---

Volume 37 | Annual Issue

Article 86

---

1930

## The Earth as a Source of Heat for Outbuildings

L. V. Crum  
*Iowa State College*

*Let us know how access to this document benefits you*

Copyright ©1930 Iowa Academy of Science, Inc.

Follow this and additional works at: <https://scholarworks.uni.edu/pias>

---

### Recommended Citation

Crum, L. V. (1930) "The Earth as a Source of Heat for Outbuildings," *Proceedings of the Iowa Academy of Science*, 37(1), 315-316.

Available at: <https://scholarworks.uni.edu/pias/vol37/iss1/86>

This Research is brought to you for free and open access by the Iowa Academy of Science at UNI ScholarWorks. It has been accepted for inclusion in Proceedings of the Iowa Academy of Science by an authorized editor of UNI ScholarWorks. For more information, please contact [scholarworks@uni.edu](mailto:scholarworks@uni.edu).

about 430 meters per second at 26°C. For ether vapor the value is 195 meters per second at 23°C. These values are about five per cent higher than the values given in the International Critical Tables.

By using the velocity formula we get 428 meters per second for

$$V = \sqrt{\frac{\alpha p}{d}}$$

the velocity in water vapor at 25°C ( $V=1.321$ ), a value which is in satisfactory agreement with the experimental value. For ether vapor at 35°C ( $V=1.093$ ) the formula gives 199 meters per second which agrees within the limits of experimental error with the experimental result after correction is made for the difference of temperature.

IOWA STATE COLLEGE,  
AMES, IOWA.

---

## MEAN FREE PATH OF GASES BY A DIRECT METHOD

JOHN A. ELDRIDGE

Apparatus consists of a brass tube partitioned into chambers. Partitions contain small holes which are exactly aligned. Gas is introduced at a pressure of several millimeters at one end; a vacuum is maintained in other chambers by rapid pumping and the molecular beam passing through the aligned holes is measured by impact upon a vane suspended from a quartz fiber. Introduction of a gas in one of intermediate chambers deflects away a definite proportion of the beam giving a direct measure of the mean free path.

STATE UNIVERSITY OF IOWA,  
IOWA CITY, IOWA.

---

## THE EARTH AS A SOURCE OF HEAT FOR OUT-BUILDINGS

L. V. CRUM

The object of this experiment was to investigate the possibilities of utilizing the earth's heat near the surface to warm chicken houses, garages, and other out-buildings during extremely cold weather.

A section of water radiator was buried in a trench seven feet deep which was dug in the dirt floor of a henhouse. Directly above

this another similar radiator was mounted and connected by two inch pipes to the lower radiator. The radiators were filled with kerosene and were ready for operation January 1, 1930.

During the following weeks of cold weather the temperature of the kerosene in the upper radiator was recorded and at no time was it found to be as low as 30°F. The lowest temperature noted in the chicken house was 14°F while on the outside it was -23°F.

That end of the chicken house which contained the radiator was later insulated from the remainder which was to be used as a control. But since the installation of this partition the weather has been so warm that it has been impossible to obtain any accurate data on the effectiveness of this arrangement in keeping the room warm.

IOWA STATE COLLEGE,  
AMES, IOWA.

---

## PROBLEMS SUGGESTED BY AN UNCERTAINTY PRINCIPLE IN ACOUSTICS

G. W. STEWART

At the suggestion of Professor A. Lande the principle adopted is  $\Delta v \cdot \Delta t = 1$ , where  $v$  is the intrinsic frequency of an acoustic signal and  $\Delta t$  is its time duration. Applying this principle one finds that it is consistent with experiments on the change in  $v$  in the vibrato and the failure to detect it by ear, with recorded tests on minimum perceptible differences in frequency, and with the minimal time for tone perception. The problems suggested by the principle are: (1) Variations in  $\Delta t$  and  $\Delta v$  by an artificial vibrato with aural observations of detectable  $\Delta v$ , (2) redetermination of minimum perceptible differences in frequency as dependent upon  $\Delta t$  and (3) an examination of  $\Delta t$  required for tone perception with varied values of  $\Delta v$  required for so-called tone perception.

STATE UNIVERSITY OF IOWA,  
IOWA CITY, IOWA.

---

## ON THE CONDUCTIVITY OF COD LIVER OIL

L. W. BUTLER

Further experiments have been conducted on the conductivity of cod liver oil under varying conditions. All experiments on the